



Material:

- 1.Cable: Non-UL [26(10/0.12)*1C Tinned Copper Insulation: PVC+ Spiral Shield(28/0.12) Tinned Copper]*2 Flat, Jacket; PVC OD: $\varnothing 2.8 \times 5.6 \pm 0.15$ mm Color:Black(NK-KO1)
- 2.Connectors:P1&P2: RCA Plug Nickel Plated
P3&P4: RCA Jack Nickel Plated
- 3.Hood: P1&P3: Molded Type, PVC 45P, Color: White(NK-WO1)
P3&P4: Molded Type, PVC 45P, Color:Red(NK-RO1)
- 4.Test Request: <1>. 100% Open Short & MIS Wire Test
<2> Insulation Resistance 1M min
- 5.Packing: Seep-0039 Rev.B Packing Drawing
EAN Code:4016032051329
(Binding size must be smaller than blister)
- 6.Blister Size: DB VP2

		PIN Out				PIN Out	
P1	Cond	White	P3	P2	Cond	Red	P4
	Shell	Spiral	Cond	Shell	Shell	Spiral	Cond



ITEM NO	AK-CHMF-015-R (1.5M) AK-CHMF-R (2.0M) AK-CHMF-025-R (2.5M) AK-CHMF-050-R (5.0M)
----------------	--

TITLE	Cinch Extension Cable, Molded Hoods 2 x Cinch Male to 2 x Cinch Female
--------------	---

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
© Copyright 2008 by Assmann Electronic Components
All International Rights Reserved