



PIN ASSIGNMENT:

P1	P2	P3	COLOR
1	1		RED
2		1	WHITE
3	2		DRAIN(RED)
		2	DRAIN(WHITE)

Electrical:

- 100% Short, open, miswire test
- Conduct resistance: 5Ω (Max)
- Insulation resistance: 5MΩ (Min)
- Dielectric test: 300V DC

Material:

- Cable: NOUS [(10/0.10)+S(28/0.10)]*2F
 - PVC-40P Jacket Black
 - OD 2.8*5.6MM
 - L=10,000±50MM
- P1 Connector: 3.5ST Male
 - Tray 6.0MM L=26MM
 - Mold Type Ni-Plated insulator color Black
- P2 Connector: RCA Plug Male
 - Blossom Type Ni-Plated insulator color Brown
 - In Jacket: Clear LD-PE
 - Out Jacket: PVC-40P Red
- P3 Connector: RCA Plug Male
 - Blossom Type Ni-Plated insulator color Brown
 - In Jacket: Clear LD-PE
 - Out Jacket: PVC-40P White
- Tube: Heat Shrink Black OD1.5*10MM
- S/R: Black PVC 40P

Unit: MM

RoHS
Compliant

ITEM NO.

AK243-10M-R

TITLE

Stereo Connection Cable - 10 Meters,
3.5ST Male <=> 2x RCA Male

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
©Copyright 2010 by Assmann Electronic Components
All International Rights Reserved