

A

USB A Type Male
Plastic: White

1,800MM±30MM

USB A Type Female
Plastic: White

A

P1

P2

B

B

C

C

D

D

E

E

F

F

PIN OUT

	P1		P2	
RED	1		1	VCC
WHITE	2		2	-DATA
GREEN	3		3	+DATA
BLACK	4		4	GROUND
SHELL	BRAID		SHELL	

Material:

- Cable: UL-2725 [28AWG(7/0.127)*1PR+24AWG(7/0.203)*2C
+AL-FOIL/MYLAR+DRAIN WIRE(7/0.127)+65% BRAID]TIN
- OD: 4.7±0.15MM
- PVC Jacket
- Color: Beige
- P1 Connector: USB A Type Male
- Gold Plated 30μ" Contact
- Nickel Plated Shell
- P2 Connector: USB A Type Female
- Gold Plated 30μ" Contact
- Nickel Plated Shell
- Hood: Molded Type, PVC 45P, Color Beige
- Tooling Cavity indication for inspection

Electrical:

- 100% Open short & mis wire test
- Contact Resistance: 3Ω Max.
- Insulation Resistance: 20MΩ Min.

Scale	1:1							Name
TOLERANCE						Drawn	08.29.11	Chappel
X.X	±0.40					Approved	10.19.11	Warner
X.XX	±0.25							
X.XXX	±0.15							
Angle	±3°					 		
			Modification	Date	Name			

Item No.	Item Description	Unit	Quantity	Rate	Amount
----------	------------------	------	----------	------	--------

AK669/2-18-R

Title	Hi-Speed USB 2.0 Extention cable, 1.8 Meters, Beige, USB A Male <=> USB A Female
--------------	--

Drawing No.

rev00

Replace

Sheet

RoHS Complaint

ASSMANN
VVS components

H